

# Take the *Bite* out of *Deck* *Problems!*

- *Deck Fix* reduces 90% of the most common paint complaints.
- *Deck Fix* will double or triple the job life of most painting projects.
- *Deck Fix* reduces the cost of painting by extending the life of the job.
- *Deck Fix* uses patent-pending *Weather Smart™ Resin Technology* to solve painting problems. *Weather Smart™* grips on to the problem areas like glue and remains flexible.
- Deck problems don't stand a chance against *Deck Fix!*

**Ask to see  
and touch a sample  
board and jar.**

We Welcome your Questions  
**Call or Email Today!**

**(507) 645-7431**

**[questions@maddogprimer.com](mailto:questions@maddogprimer.com)**

**[www.maddogprimer.com](http://www.maddogprimer.com)**



**Stops  
Decks From  
Peeling!**

## Deck Fix™

**Jobs last 2-3 Times Longer  
with Weather Smart™ technology**

### Exterior Deck Primer



- **Earth-Friendly Primer** •
- **Low VOC** •
- **Soap and Water Clean-up** •

Patent Pending

**Stops Rust &  
Tannin Bleed**



Cupcake – French Mastiff

## Solve Everyday Problems:

- Peeling deck surfaces
- Rusty nail head bleeding
- Peeling deck railings

## Benefits

- Reduces 90% of common paint problems
- Low-cost, long-term alternative
- Projects last 2-3 times longer with *Deck Fix*
- Earth-Friendly Formula, Low VOCs (<48 g/l)
- Soap and water clean-up
- Breathable to vapor

## Frequently Asked Questions:

*The information below should not be considered complete. Technical specification answers, specific application guidelines, Material Safety Data Sheets (MSDS) and warranty information, etc. are found at [www.maddogprimer.com](http://www.maddogprimer.com).*

### How much preparation is needed?

Prepare as you normally would, following normal painting practices. Follow all safety guidelines.

- Wash and clean areas
- Remove all mold and mildew
- Knock down rust from nail heads
- Scrape and sand until area is stable
- Sand area to your desired smoothness
- Sand glossy areas and finishes
- Let all areas dry to below 15% moisture content

**How is *Deck Fix* applied?** *Deck Fix* can be applied with a brush and roller. Work *Deck Fix* into the substrate so it can penetrate and adhere better.

**Do I need to apply *Deck Fix* to all surfaces?** Yes. Apply *Deck Fix* to the entire project.

**How many coats of *Deck Fix* do I need?** Generally one coat is enough to stabilize the problem surface. Apply a second coat to badly worn, cracking, or peeling areas.

**How much *Deck Fix* will I need?** *Deck Fix* has a coverage of 300-350 SF per gallon.

**How thick should it be applied?** Apply a thin coat of *Deck Fix* to the deck surface. If another coat is needed for tough areas, apply an additional thin coat.



Cupcake

**How long does it take to dry?** *Deck Fix* goes on a milky brown and dries clear in about 1 hour. Recoat in 2 hours.

**Should *Deck Fix* be tacky after it dries?** Yes, *Deck Fix* might be clear and dry, but continues to be tacky.

**Can I tint *Deck Fix*?** No. We do not recommend tinting the product.

**What products can I apply over *Deck Fix*?** Apply a high-quality 100% solid latex decking stain. We do not recommend using oil-based, solvent-based or two-part "hot" products. These products do not have enough flexibility and could crack/crackle.

Check all coatings for compatibility with *Deck Fix* before proceeding with entire project.

**How many coats of solid latex decking stain do I need?** We recommend 2 coats of decking stain on top of *Deck Fix* to get the best results.

**Will *Deck Fix* stop rust on nail heads?** *Deck Fix* will stop rust when 2 coats are applied. Hint: touch up the nail heads first and then apply one thin coat of *Deck Fix* to the entire deck top. This way you'll get two coats on the nail heads and only one coat on the deck.

**Footwear:** *Deck Fix* will remain tacky until topcoated. We recommend you wear only socks when applying the 1st finish coat of solid latex decking stain. Your socks are more forgiving to the tacky primer and will not tear up the *Deck Fix* from the deck surface.

**For best results:** Pressure wash and/or strip deck surfaces and remove all coatings and dead wood fibers down to fresh pink wood. Apply 1 coat of *Deck Fix* in the morning and apply the 1st coat of solid latex decking stain a few hours later. Let dry overnight. The next day, apply the 2nd coat of stain.