

**MATERIAL SAFETY DATA SHEET**  
FOR COATINGS, RESINS, AND RELATED MATERIALS NPCA 1-84

MANUFACTURER'S NAME  
Mad Dog Paint Products  
309 Plum Street North  
Northfield, MN 55057

EMERGENCY TELEPHONE NO.  
  
(507) 645-7431

DATE OF PREPARATION  
  
January 2008

INFORMATION TELEPHONE NO.  
  
(507) 645-7431

---

**SECTION I --- PRODUCT IDENTIFICATION**

---

PRODUCT CODE            MDP-01  
  
PRODUCT NAME            Mad Dog Primer  
  
PRODUCT CLASS            Water Thinned Paints

---

**SECTION II --- HAZARDOUS INGREDIENTS**

---

INGREDIENT		PERCENT
NAME	CAS #	
Texanol	25265-77-4	≥ 1%
Propylene Glycol	57-55-6	≥ 1%

---

**SECTION III --- PHYSICAL DATA**

---

BOILING POINT:            100 deg. C (212 deg. F)  
VAPOR DENSITY:            Lighter than Air  
EVAPORATION RATE:        Equal to Water  
% VOLATILE VOLUME:    55                            WT/GAL: 8.8 lbs            VOC: 0.40 lbs/gal (48 gr/l)

---

**SECTION IV --- FIRE AND EXPLOSION HAZARD DATA**

---

NFPA FLAMMABILITY CLASSIFICATION:    COMBUSTIBLE LIQUID - CLASS 111B  
FLASHPOINT:                    OVER 225 DEG. F.    SFCC  
EXTINGUISHING MEDIA:  
    Use NFPA Class B Fire extinguishers (carbon dioxide all purpose dry chemical or alcohol foam) designed to extinguish flammable liquid fires. Polymer foam is preferred for large fires.  
UNUSUAL FIRE AND EXPLOSION HAZARDS:  
    During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

---

**SECTION IV --- FIRE AND EXPLOSION HAZARD DATA (CONTINUED)**

---

**SPECIAL FIREFIGHTING PROCEDURES**

Firefighters should wear self-contained breathing apparatus. Water may be ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

---

**SECTION V --- REACTIVITY DATA**

---

**STABILITY**

Normally stable

**CONDITIONS TO AVOID**

Avoid excessive heat and sources of ignition

**INCOMPATIBILITY (MATERIALS TO AVOID)**

None known

**HAZARDOUS DECOMPOSITION PRODUCTS**

Burning, including when heated by welding or cutting, will produce smoke, carbon monoxide and carbon dioxide

**HAZARDOUS POLYMERIZATION**

Will not occur

**CONDITIONS TO AVOID**

None known

---

**SECTION VI --- HEALTH HAZARD DATA**

---

**EFFECTS OF SHORT TERM OVEREXPOSURE****SWALLOWING**

Unknown

**INHALATION**

Unknown

**EYE**

Unknown

**SKIN**

Unknown

**EFFECTS OF OVEREXPOSURE --- ACUTE:**

Inhalation --- Irritation of the respiratory tract

Skin and Eye Contact --- Primary irritation

Ingestion of large amounts could cause serious injury

**EFFECTS OF OVEREXPOSURE --- CHRONIC:**

None known

**MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:**

None expected when used in accordance with Safe Handling and Use (Section IX)

PRIMARY ROUTE (S) OF ENTRY:      DERMAL              INHALATION              INGESTION

---

**SECTION VII --- FIRST AID AND EMERGENCY PROCEDURES**

---

**SWALLOWING**

If swallowed call Poison Control Center, Hospital Emergency Room, or Physician immediately.  
Drink 1 or 2 glasses of water to dilute.

**INHALATION**

Remove to fresh air immediately. Get medical help for any breathing difficulty.

**EYE**

Flush with water until relieved. Consult a physician.

**SKIN**

Wash with soap and water.

**NOTES TO PHYSICIAN:**

Any treatment that might be required for overexposure should be directed at the control of symptoms and the clinical conditions.

---

**SECTION VIII --- ENVIRONMENTAL PROCEDURES**

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Confine in small area: use absorbent to clean up. Place in container for disposal.

**WASTE DISPOSAL METHOD**

Dispose in accordance with federal, state and local laws.

**RCRA CLASSIFICATION**

As produced, this product is not a waste. If discarded as is, it is not classified a hazardous waste under RCRA.

**ENVIRONMENTAL HAZARDS**

None known

---

**SECTION IX -- SAFE HANDLING AND USE INFORMATION**

---

**RESPIRATORY PROTECTION**

Use NIOSH approved respirator specified for protection against paint spray mist and sanding dust in restricted or confined areas.

**VENTILATION**

Provide general dilution and local exhaust ventilation in sufficient volume and pattern to maintain concentrations of hazardous substances listed in Section II below the lowest exposure limits stated.

**PROTECTIVE GLOVES:** Waterproof during repeated contact

**EYE PROTECTION:** Splash goggles or safety glasses with side shields

**OTHER PROTECTIVE EQUIPMENT:** Clothing adequate to protect skin

**HYGIENIC PRACTICES:** Remove and wash clothing before reuse. Wash hands before eating, smoking or using the washroom.

---

**SECTION X --- SPECIAL PRECAUTIONS**

---

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Do not throw or drop containers.

**OTHER PRECAUTIONS**

Avoid contact with eyes and prolonged contact with skin or breathing of spray mist or sanding dust. Close container after each use. Keep out of reach of children. Do not take internally.

---

**SECTION XI --- OTHER INFORMATION**

---

**US DOT INFORMATION**

HAZARD CLASS: NOT HAZARDOUS BY DOT

ID NIUMBER: UN 1263

PROPER SHIPPING NAME: PAINT

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. WHILE THE INFORMATION IS BELIEVED TO BE RELIABLE, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SINCE THE USE OF THIS INFORMATION AND THE CONDITIONS AND USE OF THIS PRODUCT ARE CONTROLLED BY THE USER, IT IS THE USER'S OBLIGATION TO DETERMINE THE CONDITIONS OF SAFE USE OF THE PRODUCT.